

XRAY XT8

FRONT

OFFSET

STANDARD ☐

+1 ☐

+2 ☐

STEERING BLOCK

PLASTIC ☐

ALU ☐

CAMBER LINK LOCATION 2 1

FRONT LOWER SHOCK POSITION 3 2 1

MEASURE UNDER ARM

FRONT DROOP

UPPER SHOCK POSITION 8 7 6 5 4 3 2 1

REAR ROLL CENTER 7 8 9 10 11 12

REAR LOWER SHOCK POSITION 1 2 3

MEASURE UNDER ARM

REAR DROOP

WHEEL

UPRIGHT ROLL CENTER

OUTBOARD TOE-IN

0° ☐ 2° ☐

REAR

OFFSET

STANDARD ☐

+1 ☐

+2 ☐

OPTIONAL ALU UPRIGHT

FRONT TOE-IN

COMPOSITE STANDARD

2° ☐

3° ☐

REAR TOE-IN

OPTIONAL ALU

2° ☐ 2.5° ☐ 3° ☐ 3.5° ☐ 4° ☐

LEFT SIDE MUST BE OPPOSITE TO THE RIGHT SIDE

CASTER ECCENTRIC BUSHING

LEFT = RIGHT

+2° ☐ +1° ☐ 0° ☐ -1° ☐ -2° ☐

FRONT ROLL CENTER

LEFT = RIGHT

BRACE

PLASTIC ☐

ALU ☐

TORQUE ☐

KICK-UP OPTION

LEFT = RIGHT

WHEELBASE SHIM POSITION

FRONT ☐ REAR ☐

KICK-UP STANDARD

5° ☐ 4° ☐

ANTI-SQUAT OPTION

LEFT = RIGHT

4° ☐ 3° ☐ 2° ☐

BRACE

PLASTIC ☐

ALU ☐

WING MOUNTING

LEFT = RIGHT

F3 F4 R3 R4 F1 F2 R1 R2

WING SHIM

YES ☐ NO ☐

WHEELBASE SHIM POSITION

FRONT ☐ REAR ☐

FRONT TOE

OUT ☐ IN ☐

SHIM UNDER STEERING PLATE

mm

STEERING PLATE

STANDARD ☐ 3D ☐

ACKERMANN POSITION

3 2 1

SERVO SAVER

TIGHT ☐ MEDIUM ☐ SOFT ☐

FRONT UPPER ARM POSITION

1mm ☐ 2mm ☐ 3mm ☐

SHIMS BEHIND ARM

REAR TOE

IN ☐ OUT ☐

REAR UPRIGHT POSITION

WHEELBASE

0 ☐ 1 ☐ 2 ☐

FRONT CAMBER

+ ☐ - ☐

SHOCK SPACER

mm

FRONT RIDE HEIGHT

mm

REAR CAMBER

+ ☐ - ☐

REAR RIDE HEIGHT

mm

COMMENTS